


TYPICAL UTILITIES LOCATION

NOTES:

1. INSTALL WATERLINE IN PLANTER STRIP WITH 4 FEET (TOP OF PIPE) MIN. COVER.
2. SEPARATE WATERLINE FROM SEWER AND STORM WATER LINES ACCORDING TO STATE DEQ REQUIREMENTS.
3. PLACE WATERLINE VALVES WITH COLLARS IN PLANTER STRIP.
4. INSTALL SEWER ACCORDING TO SOUTH VALLEY SEWER DISTRICT STANDARDS AND REQUIREMENTS.
5. PROVIDE A MIN. 2' COVER OVER THE TOP OF STORM WATER PIPES.
6. PLACE STORM WATER PIPE BELOW THE CURB AND GUTTER. INSTALL STORM WATER INLET BOXES BELOW CURB AND GUTTER EXTENDING THE BOX INTO THE ROADWAY.
6. CONSULT WITH THE ENGINEER OR HIS DESIGNEE FOR ANY CHANGES TO UTILITY PLACEMENT.
7. PROVIDE TRACER WIRE FOR SERVICE LINE.
8. PLACE SERVICE METER ASSEMBLY PER CITY STANDARDS AND AT LEAST 3- FEET FROM ANY DRIVEWAYS, APPROACHES OR ANY OTHER DRIVABLE PAVED AREA.
9. PLACE FIRE HYDRANT ON THE SAME SIDE AS THE WATERLINE
10. TREES ARE TYPICALLY PLACED IN THE CENTER OF THE PARK STRIP.
11. THE CITY ENGINEER MAY APPROVE SPECIFIC DESIGNS WHEN VARIATIONS FROM THE STANDARDS ARE NEEDED DUE TO SITE CONDITIONS, UTILITY, OR TOPOGRAPHICAL CONSTRAINTS. ANY VARIANT OF THESE DETAILS MUST BE BASED UPON A DESIGN STAMPED BY A UTAH LICENSED PROFESSIONAL CIVIL ENGINEER.



City of Bluffdale
Engineering Standards
Approved *Michael Lopez* *6/11/13*
City Engineer Date

STANDARD DETAIL TITLE
TYPICAL UTILITY PLACEMENT

DETAIL SERIES
STREET
DETAIL NO
ST-6B